



## Rheoline MDR Smart Auto-Test



### A Trusted Name in Material Testing

- Prescott Instruments is a U.K. company with **over 30 years' experience in material testing**.
- We manufacture all instruments **onsite in the U.K. under ISO 9001** and our in-house laboratory team perform all **instrument calibrations under ISO 17025**.
- Our **Moving Die Rheometer Smart Auto-Test** streamlines the testing process for rubber laboratory professionals.
- Its **precision, reliability and durability** make it an indispensable instrument for rubber laboratories of any size.

### Built to Last

- **Durability:** The high-stiffness steel frame is robust enough to withstand the demands of a busy production environment with the high precision performance to match.
- **Reliability:** Expertly-crafted construction provides stability and reliability even when testing the hardest of materials.
- **Unique:** Our bespoke high-end electronics ensure the highest data sampling rates available.

### Repeatability and Connectivity



- The **cost-effective choice** for any testing laboratory, this compact instrument **increases laboratory productivity** through its **semi-automatic sample-loading mode (4 samples at a time)**.
- Maintain **accuracy and reproducibility** by using film for loading, **preventing slippage** often found in other automated systems.
- **Simplicity of design** means you can replace components **easily and affordably**.
- **Perform tests on demand** with our built-in **Labline** analytical software.
- Data is calculated in real-time, displaying **live data traces on screen**.
- After the test is complete, the sample is removed from the test chamber and conveyed along on the film, with the **results automatically graded as pass or fail**.

# Rheoline MDR Smart Auto-Test

## Technical Specification

<b>Standards</b>	ISO No. 6502 / ASTM D5289
<b>Sample Capacity</b>	4
<b>Die Configuration</b>	Sealed 4.5cm <sup>3</sup>
<b>Oscillation Frequency</b>	1.67 Hz
<b>Oscillation Amplitude</b>	0.5, 1.0, 3.0 degrees. (0.5 Standard, 1, 3, optional)
<b>Temperature Range</b>	Ambient to 250 °C
<b>Temperature Control</b>	3 term PID, control accuracy +/- 0.03 °C
<b>Units of Measurement</b>	Torque Inlb, dNm. Temp. Celsius, Fahrenheit. Pressure Lb/sqin., Kg/sqcm. (Optional) Time Min/Sec, Min/Decimal, Seconds.
<b>Output Type</b>	Real time display of: - Elastic torque - Viscous torque - Tangent delta - Cure Rate - Pressure in Cavity (optional)
<b>Data Format</b>	All data stored in Access database with full export functionality
<b>PC Specification</b>	Pentium Processor, networkable
<b>Electrical</b>	Single Phase 220/240V 50 Hz or 110V 60 Hz
<b>Pneumatics</b>	Filtered Air; 4.2 Kg/cm, (60 Psi)
<b>Optional Extras</b>	Programmable Temperature Zones Additional Oscillation Eccentric Pressure Transducer Rheoline Volumetric Sample Cutter

**NOTICE:** Although the information and recommendations set forth herein (hereinafter "Information") are presented in good faith and believed to be correct as of the date hereof. Prescott Instruments Ltd. Make no representation or warranties as to the completeness or accuracy thereof. Information is supplied upon the conditions that the persons receiving same will make their own determination as to the suitability for their purposes prior to use. In no event will Prescott Instruments Ltd. Be responsible for damages of any nature whatsoever resulting from the use or reliance upon information for the product, equipment or system to which information refers. Nothing contained herein is to be construed as recommendation to use any product, equipment, system, process or formulation in conflict with any patent, and Prescott Instruments Ltd. makes no representation or warranty, express or implied, that the us thereof will not infringe any patent, except for the limited warranty set forth in Prescott Instruments Ltd. standard sales contracts for its equipment and services.

**PRESCOTT INSTRUMENTS LTD. MAKES NO REPRESENTATIONS OR WARRANTIES WHETHER STATUTORY, EXPRESS OR IMPLIED, OF MERCHANTABILITY FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY OTHER NATURE WITH RESPECT TO THE INFORMATION OR PRODUCT, EQUIPMENT OR SYSTEM TO WHICH INFORMATION REFERS.**

© 2016 Prescott Instruments Ltd.

**Prescott Instruments Ltd.** Unit F, Northway Trading Est, Northway Lane, Tewkesbury, Gloucestershire, GL20 8JH UK  
Tel: +44 (0) 1684 274300 ; sales@prescott-instruments.com ; www.prescott-instruments.com

